



US005868735A

United States Patent [19]

[11] Patent Number: **5,868,735**

Lafontaine

[45] Date of Patent: **Feb. 9, 1999**

[54] **CRYOPLASTY DEVICE AND METHOD**

[75] Inventor: **Daniel M. Lafontaine**, Plymouth, Minn.

[73] Assignee: **SciMed Life Systems, Inc.**, Maple Grove, Mich.

[21] Appl. No.: **812,804**

[22] Filed: **Mar. 6, 1997**

[51] Int. Cl.⁶ **A61B 17/36**

[52] U.S. Cl. **606/21; 606/26; 607/105**

[58] Field of Search 606/192, 194, 606/20-23, 26; 604/96, 101, 104; 607/104

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|-----------|---------|----------------------|---------|
| 3,125,096 | 3/1964 | Antiles et al. . | |
| 4,860,744 | 8/1989 | Johnson et al. . | |
| 5,019,042 | 5/1991 | Sahota | 604/101 |
| 5,078,713 | 1/1992 | Varney | 606/23 |
| 5,108,390 | 4/1992 | Potocky et al. . | |
| 5,139,496 | 8/1992 | Hed . | |
| 5,147,355 | 9/1992 | Friedman et al. . | |
| 5,190,540 | 3/1993 | Lee . | |
| 5,281,215 | 1/1994 | Milder . | |
| 5,334,181 | 8/1994 | Rubinsky et al. | 606/22 |
| 5,334,193 | 8/1994 | Nardella . | |
| 5,417,689 | 5/1995 | Fine . | |
| 5,423,807 | 6/1995 | Milder | 606/20 |
| 5,443,470 | 8/1995 | Stern et al. | 607/98 |
| 5,454,807 | 10/1995 | Lennox et al. . | |
| 5,501,681 | 3/1996 | Neuwirth et al. | 606/21 |
| 5,536,252 | 7/1996 | Imran et al. | 604/101 |
| 5,624,392 | 4/1997 | Saab . | |

OTHER PUBLICATIONS

A. Schilling et al., "Nature of the Vehicle for Cryopreservation of Human Peripheral Veins: Preservation of Reactivity to Pharmacological Stimuli" *Cryobiology* 32, 109-113 (1995).

P. Nataf et al., "Effect of Cold Anoxia and Cryopreservation on Metabolic and Contractile Functions of Human Mammary Artery", *Cryobiology*, 32, 327-333, (1995).

Mazur, P., Physical-Chemical Factors Underlying Cell Injury in Cryosurgical Freezing, *Cryosurgery*, pp. 32-51, published on date even with or prior to Mar. 6, 1997.

Cahan, W., "Five Years of Cryosurgical Experience: Benign and Malignant Tumors with Hemorrhagic Conditions", *Cryosurgery*, pp. 388-391, published on date even with or prior to Mar. 6, 1997.

Zacarian, S., "Cryosurgery of Tumors of the Skin and Oral Cavity", 5 pages, published on date even with or prior to Mar. 6, 1997.

B. Fuller et al., "Clinical Applications of Cryobiology", 4 pages, published on date even with or prior to Mar. 6, 1997.

G. Morris et al., "Effects of Low Temperatures on Biological Membranes", 2 pages, published on date even with or prior to Mar. 6, 1997.

R. Cogger et al., "Preservation Techniques for Biomaterials", *The Biomedical Engineering Handbook*, 8 pages, 1995.

C. Hunt et al., "Fractures in Cryopreserved Arteries", *Cryobiology*, 31, 506-515 (1994).

Article entitled "Prostate Cryosurgery now Reimbursable in Southern California", *Healthcare Technology Management*, published on date even with or prior to Mar. 6, 1997, 1 page. Abstract entitled "Renal Cryoablation in a Canine Model", *Urology*, May 1996, 1 page.


(List continued on next page.)

Primary Examiner—John P. Lacyk
Assistant Examiner—Roy D. Gibson
Attorney, Agent, or Firm—Crompton, Seager & Tufte

[57] **ABSTRACT**

A cryoplasty catheter and method for preventing or slowing reclosure of a lesion following angioplasty. The cryoplasty catheter includes a shaft having proximal and distal ends and a dilatation balloon disposed at the distal end. An intake lumen and exhaust lumen are defined by the shaft to deliver coolant to the balloon and to exhaust or drain coolant from the balloon. The method in accordance with the present invention includes cooling a lesion to aid in remodeling the lesion through dilatation and/or freezing a portion of the lesion adjacent the dilatation balloon to kill cells within the lesion to prevent or retard restenosis.

7 Claims, 2 Drawing Sheets



OTHER PUBLICATIONS

Abstract entitled "Cox Maze Operation Without Cryoablation for the Treatment of Chronic Atrial Fibrillation", *Annals of Thoracic Surgery*, Aug. 1995, 1 page.

Abstract entitled "Percutaneous Serial Catheterization in Swine: a Practical Approach", *Journal of Investigative Surgery*, Mar.-Apr. 1995, 1 page.

Abstract entitled "Cardiac Rhythm Disturbances due to Caval Occlusion During Hepatic Cryosurgery", *Cryobiology*, Oct. 1994, 1 page.

Abstract entitled "Intractable Chest Pain in Cardiomyopathy: Treatment by a Novel Technique of Cardiac . . .", *British Heart Journal*, Dec. 1993, 1 page.

Abstract entitled "Histologic Study of Chronic Catheter Cryoablation of Atrioventricular Conduction in Swine", *American Heart Journal*, Jun. 1993, 1 page.

Abstract entitled "Argon Beam Coagulation Compared with Cryoablation of Ventricular Subendocardium", *Annals of Thoracic Surgery*, Jan. 1993, 1 page.

Fig. 1




Fig. 2




Fig. 3





Fig. 4



CRYOPLASTY DEVICE AND METHOD

FIELD OF THE INVENTION

The present invention pertains generally to the field of angioplasty and, in particular, to a form of angioplasty involving lesion cooling.

BACKGROUND OF THE INVENTION

Conventional angioplasty has been preformed for several decades, prolonging the lives of an ever increasing number of patients. Angioplasty procedures involves the dilatation of a balloon placed across a lesion in a coronary artery. Dilatation of the balloon in turn dilates the lesion, opening the artery for increased blood flow. In some cases, however, the goal of the angioplasty procedure is, in whole or in part, frustrated by complete or partial reclosure of the artery at the lesion. Two mechanisms are believed to be principally responsible for reclosure of the artery, these are restenosis and recoil. Restenosis is believed to be caused by continued growth or regrowth of the smooth muscle cells associated with the lesion. Recoil is in part a mechanical process involving elastic rebound of the dilated lesion.

Several means have been disclosed for addressing the problem of restenosis. These include, among others, radiation treatments to slow or prevent smooth muscle cell proliferation associated with the restenotic process. Certain drug therapies have been proposed to prevent or slow restenosis.

Several means have also been developed to address the issue of recoil. One of the more significant developments in this area has been stents, which can be permanently deployed to mechanically hold open lesions. Although stents have been found to be highly effective, they may irritate the wall of a artery in which they are implanted. Some believe that this may encourage limited restenosis. Warming of the lesion during dilatation has also been disclosed to prevent or slow recoil. Warming the lesion is believed to soften the lesions such that it may be "remodeled" that is, thinned under low pressure. Heating of the lesion, however, is believed to cause an injury response which may cause some restenosis.

SUMMARY OF THE INVENTION

The present invention is directed at an apparatus and method for performing angioplasty and preventing or slowing the post-procedure reclosure of a dilated lesion. The present invention cools the lesion to prevent or slow reclosure by the mechanisms of restenosis or recoil. A cryoplasty catheter is provided to cool the lesion to aid in remodeling the lesion to prevent or slow recoil. The present invention can also be used to cool the lesion to freeze a portion of the lesion tissue. This is believed to kill cells within the lesion which would promote restenosis.

A preferred embodiment of the cryoplasty catheter in accordance with the present invention includes a shaft having proximal and distal ends. The shaft defines an inflation lumen, coolant intake lumen and exhaust lumen therethrough. Each lumen has a proximal and distal end proximate the proximal and distal ends of the shaft respectively. A dilatation balloon is disposed at the distal end of the shaft and is in fluid communication with the inflation lumen. A chamber is disposed within the balloon and is in fluid communication with the intake and exhaust lumens. A source of coolant is connected to the proximal end of the shaft in fluid communication with the coolant intake lumen.

A thermo-resistive sensor can be disposed on the dilatation balloon to monitor the temperature of the lesion. A second thermo-resistive sensor can be disposed on the shaft to provide a control temperature reading.

In another preferred embodiment of the cryoplasty catheter in accordance with the present invention, the cryoplasty catheter includes a shaft having proximal and distal ends. The shaft defines an inflation lumen and a drain lumen therethrough. Each lumen has a proximal and a distal end proximate the proximal and distal ends of the shaft respectively. A dilatation balloon is disposed at the distal end of the shaft and is in fluid communication with the inflation and drain lumens. The cryoplasty catheter also includes a coolant source connected to the proximal end of the shaft in fluid communication with the inflation lumen.

This embodiment of the cryoplasty catheter can also include a thermo-resistive sensor disposed on the dilatation balloon. As well as the thermo-resistive sensor disposed on the balloon, a control sensor can be disposed on the catheter shaft.

A method of performing cryoplasty is also provided which includes the steps of advancing a cryoplasty catheter across a lesion, inflating the dilatation balloon to dilate the lesion, and delivering coolant to the balloon to cool the lesion. To aid in remodeling, the lesion adjacent the balloon can be cooled to between 10° C. and -10° C. A portion of the lesion adjacent the balloon can also be frozen to kill cells within the lesion which would otherwise promote restenosis. For enhanced effectiveness, freezing may be done by flash freezing the tissue for 20 to 60 seconds. The cells are preferably frozen at a temperature of between -20° C. and to -40° C.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a cryoplasty catheter in accordance with the present invention;

FIG. 2 is a longitudinal cross-sectional view of the distal end of the cryoplasty catheter of FIG. 1;

FIG. 3 is an alternate embodiment of a cryoplasty catheter in accordance with the present invention; and

FIG. 4 is an alternate embodiment of a cryoplasty catheter in accordance with the present invention including a surrounding vacuum lumen.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings wherein like reference numerals refer to like elements throughout the several views, FIG. 1 is a side view of a cryoplasty catheter 10 in accordance with the present invention. Shaft 12 has a proximal end and a distal end. A dilatation balloon 14 is disposed at the distal end of shaft 12. At the proximal end of shaft 12 is a manifold 16. Connected to manifold 16 is a pump 18, which can be hand pumped for inflating balloon 14. A coolant source 20 is also connected to manifold 16 which, as explained below, provides a supply of coolant to balloon 14. Catheter 10 can be provided with a thermo-resistive temperature sensor 22 for monitoring the temperature of a lesion and a thermo-resistive control sensor 24 connected to a monitor 26.

FIG. 2 is a longitudinal, cross-sectional view of the distal end of catheter 10 including the distal end of shaft 12 and balloon 14. Shaft 12 includes an outer tube 28 which defines an inflation lumen 30 in fluid communication with the interior of balloon 14. A guidewire tube 32 defining a

guidewire lumen **34** can extend through at least a portion of shaft **12** to distal of balloon **14**. A marker band **36** can be disposed on guidewire tube **32** within balloon **14**.

Shaft **12** also includes a coolant intake tube **38** defining a coolant lumen **40** in fluid communication with a cooling chamber **42** disposed within balloon **14**. Shaft **12** also includes an exhaust or drain tube **44** which defines an exhaust or drain lumen **46** in fluid communication with chamber **42**. At the distal end of tube **38** is an orifice **48** which preferably has a diameter smaller than that of an orifice **50** at the distal end of tube **44**. The diameter of orifice **48** could be, for example, about 0.004 inches, or larger or smaller depending upon the diameter of orifice **50**.

Those skilled in the art will recognize the various materials which can be advantageously used to make the catheter of the present invention. Those elements not found in conventional angioplasty catheter such as coolant intake tube **38**, chamber **42** and exhaust tube **44** can also be made from materials known to those skilled in the art. For example, inlet tube **38** can be a hypotube or polyimide tube having an inside diameter of, for example, between 0.001 to 0.020 inches, but preferably between 0.002 and 0.010 inches. Exhaust tube **44** can be made from polyimide and have an inside diameter which is preferably greater than the inside diameter of inlet tube **38**. The chamber **42** can be made from polyimide. These materials and dimensions should be viewed as exemplary only, as those skilled in the art would appreciate the applicability of alternative dimensions and materials for these elements.

FIG. **3** is a schematic view of another embodiment of a cryoplasty catheter in accordance with the present invention referred to by the numeral **100**. Cryoplasty catheter **100** includes a shaft **112** having a proximal distal end and a distal end. A balloon dilatation balloon **114** is disposed at the distal end of shaft **112**. Proximate the proximal end of shaft **112** is a pump **118** connected to a coolant source **120** which can include refrigeration for controlling the temperature of the coolant.

A guidewire tube **132** defines a guidewire lumen **134** extending through at least a portion of shaft **112** to the distal end of catheter **100**. A coolant intake/inflation tube **138** having a proximal end and a distal end proximate the proximal and distal ends of shaft **112** defines a coolant/inflation lumen **140**. Lumen **140** is in fluid communication with pump **118** proximate its proximal end and balloon **114** proximate its distal end. Shaft **112** also includes an exhaust/drain tube **144** defining a lumen **146** and having a proximal and distal end proximate the proximal and distal ends of shaft **112**, respectively. The distal end of lumen **146** is in fluid communication with balloon **114**. The proximal end of lumen **146** can be in fluid communication with coolant source **120** for recycling of coolant, or may be discharged for disposal. Lumen **140** has a distal orifice **148** which is preferably smaller than a distal orifice **150** of lumen **146**.

Those skilled in the art will recognize that there are numerous materials and methods of manufacture which would be suitable for production of catheter **100**. Those elements of catheter **100** which are not typical of angioplasty catheters such as inflation/intake tube **138** and exhaust/drain tube **144** can be made as described above with respect to the corresponding elements of catheter **10**. It should be noted however that tube **138** should be sized appropriately to serve its dual purpose as an inflation tube and coolant intake tube. Additionally, the sizes of tubes **138** and **144**, as well as the corresponding elements of catheter **10** should be sized to take into account the physical properties of a particular

coolant medium for example, the relative rate of heat transfer to the coolant medium from a lesion.

Another alternate embodiment **212** of a cryoplasty catheter in accordance with the present invention is shown in FIG. **4**. The cryoplasty catheter **212** is essentially similar to catheter **12** shown in FIG. **2** except that a sheath **260** surrounds tube **28** to define an annular lumen **262** between sheath **260** and tube **28**. Sheath **260** preferably extends from balloon **14** proximally to manifold **16**. Manifold **16** for this embodiment can include an additional port in fluid communication with lumen **262**. Except for the additional port, lumen **262** should be completely sealed such that a vacuum may be maintained within lumen **262** when a vacuum source is applied to the port. A vacuum can be created in lumen **262** during the procedure to provide insulation between the coolant and the patient. Sheath **262** can be made from biocompatible materials known to those skilled in the art of catheter construction which are sufficiently rigid to prevent lumen **262** from collapsing when a vacuum is created therein.

In use, dilatation balloon **14** of catheter **10** is advanced across a lesion in a conventional manner. Balloon **14** is dilated by forcing fluid into balloon **14** through inflation lumen **30** with pump **18**. Coolant is then released into chamber **42** from a pressurized container or pump (not shown) to cool the adjacent lesion at a rate appropriate to the treatment goals described in more detail below. The coolant is discharged from chamber **42** through exhaust or drain lumen **46**. The arrow in FIG. **1** proximate manifold **16** shows coolant being discharged to the atmosphere from lumen **46**. Coolant may be collected for recycling or disposal as desired.

In a preferred embodiment of the invention, the inflation fluid is a low freezing point liquid such as an ethanol mixture. The coolant is one which will provide the appropriate heat transfer characteristics consistent with the goals of treatment. Liquid N₂ can be used as a general purpose coolant with catheter **10** and is particularly useful when freezing of cells within the lesion is desired. When liquid N₂ is used in catheter **10**, it can be transported to chamber **42** in the liquid phase where it evaporates at orifice **48** and exits through lumen **46** as a gas. Freon, N₂O gas and CO₂ gas can also be used as coolants. Other coolants could be used such as cold saline solution which would enter and exit chamber **42** as a liquid, Fluisol or a mixture of saline solution and ethanol. It is anticipated that coolants such as saline solution could be used with catheter **10** when rapid freezing of cells within a lesion is not a treatment goal. One skilled in the art would appreciate that other coolants could be used in a similar manner to achieve one or more of the treatment goals.

Catheter **100** can be used in a manner similar to catheter **110**, except that the coolant must also serve as the inflation fluid. It is contemplated that in most applications involving catheter **100**, a liquid coolant such as saline solution will be used.

Temperature can be monitored by thermo-resistive sensors **22** and **24** either absolutely with pre-calibrated sensors and/or relatively between sensors **22** and **24**. Depending on the treatment goals and temperature level monitored, the flow rate of the coolant into the catheter can be adjusted to raise or lower the temperature of the lesion.

The goal of cryoplasty treatment is to prevent or retard the reclosure of a dilated lesion by preventing or retarding restenosis and/or recoil of the lesion. Cooling the lesion to near 0° C. is believed to change the characteristics of the

5

lesions in such a way as to enhance remodeling by low pressure dilatation to prevent or retard recoil of the lesion. Further cooling to freeze the lesion is believed to create apoptosis of the lesion tissue, i.e., killing cells within the lesion.

In a preferred embodiment of the method in accordance with the present invention, a cryoplasty catheter such as one described above is used to dilate the lesion and slowly cool (for example, over a 1–5 minute period) it to reduce injury to healthy tissue while altering the plaque to be more susceptible to permanent, mechanical remodeling. The temperature of the lesion during dilatation is preferred to be about 0° C. to 20° C. such that the plaque characteristics are significantly altered, but normal healthy tissue has been injury preserved.

Alternately or in addition to slow cooling to approximately 0° C. to 20° C. for enhanced remodeling, the lesion can be flash frozen to 0° C. to –40° C. for between 20 to 30 seconds while the balloon is still inflated. Saline or contrast injections may be utilized pre, or during freeze to prevent adjacent blood freezing from creating occlusive thrombus.

The mechanisms of restenosis and recoil are not fully understood. It is believed in the case of restenosis, that freezing the thrombus tissue injures the capillaries that supply the lesion tissue and promote muscle cell proliferation. With respect to recoil, it is believed that cooling the plaque makes it relatively very stiff and crystallized, thus being more susceptible to permanent remodeling.

Numerous characteristics and advantages of the invention covered by this document have been set forth in the foregoing description. It will be understood, however, that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of parts without exceeding the scope of the invention. The inventions's scope is, of course, defined in the language in which the appended claims are expressed.

6

What is claimed is:

1. A cryoplasty catheter, comprising:

a shaft having proximal and distal ends, the shaft defining an inflation lumen, coolant intake lumen and exhaust lumen therethrough, each lumen having a proximal and distal end proximate the proximal and distal ends of the shaft respectively;

a dilatation balloon disposed at the distal end of the shaft and in fluid communication with the inflation lumen; and

a chamber disposed within the balloon and in fluid communication with the intake and exhaust lumens, wherein the chamber is sized such that coolant entering the chamber from the coolant intake will evaporate in the chamber prior to exiting through the exhaust lumen.

2. The cryoplasty catheter in accordance with claim 1, further comprising a source of coolant being connected to the proximal end of the shaft in fluid communication with the intake lumen.

3. The cryoplasty catheter in accordance with claim 2, wherein the coolant source contains liquid N₂.

4. The cryoplasty catheter in accordance with claim 1, further comprising a thermo-resistive sensor disposed on the dilatation balloon.

5. The cryoplasty catheter in accordance with 4, further comprising a second thermo-resistive sensor disposed on the shaft.

6. The cryoplasty catheter in accordance with claim 1, wherein the shaft further defines a guidewire lumen.

7. The cryoplasty catheter in accordance with claim 1, wherein the shaft is at least in part surrounded by an insulating sheath which in part defines a vacuum lumen.

* * * * *